

REA STEAM CLEANING S.r.I.

via Lombardi, 6 - 10028 Trofarello (TO) ITALIA E-mail: <u>info@reasrl.eu</u> http:// <u>www.reasrl.eu</u> Tel. +39 011 6804250 - Fax. +39 011 6804292

- SATURNO SPECIAL 2 VAC heavy duty professional saturated steam 18 kW generator, for industrial, food processing, collectivities cleaning, degreasing, sanitizing and disinfecting – WITH INTEGRATED VACUUM
- 1200 W vacuum unit, 30 lt stainless steel tank, activated from the handle
- Body and boiler in Stainless steel (AISI 304)
- Magnetic anti-limescale filter
- prepared for surfaces treatments (phosphate coating, passivation, etc.)
- 2 electronically controlled boilers of 9 kW each
- 6 functions selectable from the grip handle
- Adjustable detergent mixture
- 3 phases vacuum socket, low tension on the control hand (12V) and low tension control panel (24V)
- starts in less than 4 mn, 4 hours autonomy in standard use
- 12 bar of pressure, 188°C in the boiler
- steam temperature at the nozzle: 150° C
- Steam production: 30 kg/hour





REA STEAM CLEANING S.r.I.

via Lombardi, 6 - 10028 Trofarello (TO) ITALIA E-mail: <u>info@reasrl.eu</u> http:// <u>www.reasrl.eu</u> Tel. +39 011 6804250 - Fax. +39 011 6804292

Functions selectable from the grip handle

- 1) steam only
- 2) steam + detergent
- 3) steam + water
- 4) steam + detergent + vacuum
- 5) steam + vacuum
- 6) vacuum

Technical specifications

Power supply

Power

Steam production

Water tank capacity

Water consumption

Indicator for lack of water

Detergent tank

Indicator for lack of detergent

Adjustable quantity of detergent

Vacuum

Maximum hose length

Electrical cable length

Markings and certifications

Weight

Dimensions (mm)

400 V / 28 A /50 Hz (other on request)

18 kW

30 kg/hour, 188°C in the boiler, 12 bar of pressure

100 lt, 4 hours autonomy in standard use

30 lt/hours

ves

10 lt

yes

yes

1200 W, 220 v, 30 lt stainless steel tank

12 mt

10 mt

CE - PED - IPX 5

165 kg

L 1280 x W 745 x H 1020

OPTIONS

Kit for linked to the water feeding (continuous operation)

Kit for surface treatment (phosphating, passivation, etc.)